

**TO-92 CASE** 



www.centralsemi.com

#### DESCRIPTION:


The CENTRAL SEMICONDUCTOR 2N3414, MPS3414 series devices are silicon NPN transistors, manufactured by the epitaxial planar process, designed for general purpose and switching applications.

#### MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T <sub>A</sub> =25°C unless otherwise	noted) SYMBOL	2N3414 2N3415 MPS3414 MPS3415	2N3416 2N3417 MPS3416 MPS3417	UNITS
Collector-Base Voltage	V <sub>CBO</sub>	25	50	V
Collector-Emitter Voltage	VCEO	25	50	V
Emitter-Base Voltage	V <sub>EBO</sub>	5.0		V
Continuous Collector Current	IC	500		mA
Power Dissipation	PD	625		mW
Power Dissipation (T <sub>C</sub> =25°C)	PD	1.5		W
Operating and Storage Junction Temperature	TJ, Tstg	-65 to +150		°C

ELECTRICAL CHARACTERISTICS: (T <sub>A</sub> =25°C unless otherwise noted)						
SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS		
I <sub>CBO</sub>	V <sub>CB</sub> =Rated V <sub>CBO</sub>		100	nA		
I <sub>EBO</sub>	V <sub>EB</sub> =5.0V		100	nA		
BVCEO	I <sub>C</sub> =10mA (3414, 3415)	25		V		
BVCEO	I <sub>C</sub> =10mA (3416, 3417)	50		V		
V <sub>CE(SAT)</sub>	I <sub>C</sub> =50mA, I <sub>B</sub> =3.0mA		0.3	V		
V <sub>BE</sub> (SAT)	I <sub>C</sub> =50mA, I <sub>B</sub> =3.0mA		0.85	V		
h <sub>FE</sub>	V <sub>CE</sub> =4.5V, I <sub>C</sub> =2.0mA (3414, 3416)	75	225			
h <sub>FE</sub>	V <sub>CE</sub> =4.5V, I <sub>C</sub> =2.0mA (3415, 3417)	180	540			
h <sub>fe</sub>	V <sub>CE</sub> =4.5V, I <sub>C</sub> =2.0mA, f=1.0kHz (3414, 3416)	75				
h <sub>fe</sub>	$V_{CE}$ =4.5V, I <sub>C</sub> =2.0mA, f=1.0kHz (3415, 3417)	180				

R3 (10-September 2013)





# 

#### DIMENSIONS INCHES MILLIMETERS MIN MAX MIN MAX SYMBOL A (DIA) 0.175 0.205 4.45 5.21 В 0.170 0.210 4.32 5.33 0.500 С -12.70 -D 0.016 0.022 0.41 0.56 Е 0.100 2.54 F 0.050 1.27 G 0.125 0.165 3.18 4.19 0.080 0.105 Н 2.03 2.67 0.015 T 0.38

TO-92 (REV: R1)

#### 2N3414 THRU 2N3417

LEAD CODE:

1) Emitter

R1

- 2) Collector
- 3) Base

#### MPS3414 THRU MPS3417

- LEAD CODE:
- 1) Emitter
- Base
   Collector
- S) Collector

### MARKING:

FULL PART NUMBER

www.centralsemi.com

#### **TO-92 CASE - MECHANICAL OUTLINE**

R3 (10-September 2013)

#### OUTSTANDING SUPPORT AND SUPERIOR SERVICES

#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options

#### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- · Environmental regulation compliance
- Customer specific screening
- · Up-screening capabilities

· Custom product packing

Custom bar coding for shipments

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

#### REQUESTING PRODUCT PLATING

- If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when 1. ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### CONTACT US

#### **Corporate Headquarters & Customer Support Team**

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's LIMITATIONS AND DAMAGES DISCLAIMER. which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms



## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 Central Semiconductor:

 2N3417
 2N3415
 2N3416